







NOVO

TECHNICAL SPECIFICATIONS

TECHNICAL OF ECH TOTALION	
Dimensions (mm)	
Maximum Length	7305
Maximum Width	2282
Maximum Height	3350
Wheelbase	3385
Front Overhang	1650
Rear Overhang	2270
Weights (kg)	
Gross Vehicle Weight	9100
Engine	ICUZU /UKAE/D
Model	ISUZU 4HK1E6D Commonrail Turbo Diesel Intercooler
Type	4
Cylinders	
Displacement (cc) Maximum Power (kW(PS)/rpm)	5193 190 / 2600
Maximum Torque (Nm/rpm)	510 /1600-2800
Exhaust Emission Class	Euro VI OBD-D
Transmission	Edio VI OBD D
Model	ISUZU MZZ-6
Type	Manuel. Overdrive
Number of Gears	6 Forward. 1 Reverse
Steering System	
•	Hydraulic, Tilt and Telescopic
Tyres Tyre Sizes	21E/7E D17 E
Suspension	215/75 R17,5
Front	Parabolic Steel Alloy Leaf Springs
Rear	Parabolic Steel Alloy Leaf Springs
Brake System	Farabolic Steet Alloy Lear Springs
Front / Rear	Disc / Disc
System	Full Air Brake System With ABS and ESC
System	Dual Circuit, Auto-Adjusted
Parking Brake	Air Actuated, Operating on Rear Axle
Auxiliary Brake	Exhaust Brake
Fuel Tank	
Fuel Tank Capacity (lt)	150
Adblue Tank (lt)	16
Luggage Compartment	
Luggage Capacity (m ³)	3,1
Interior Luggage Racks	S
Electrical System	
Battery	24V (2 x 12V) -105 Ah
Passenger Capacity	
Standard Seat Layout	27(Passengers)+1(Driver)
Optional Seat Layouts	29(Passengers)+1(Crew)
Carry Cook	26(Passengers)+1(Crew)
Crew Seat	Opt*
Seat Layouts With Wheelchair	Opt







EQUI

EQUIPMENTS Heating and Ventilation		ANADOLU ISUZU
Pre Heater	Opt	
Convector Heater (Panel Radiator)	Opt	
Air Conditioner		

Air Londitioner	
Digital Air Conditioner	S
Safety & Driving Comfort	
Cruise Control	Opt
Speed Limitor	S
Tachograph	S
ABS	S
ASR	Opt S S S S S S
ESC/ESP	S
EBD	S
AEBS	S
LDWS	
Retarder	Opt
Parking Sensor	Opt
Immobiliser	S
Fire Extinguisher	Opt
Engine Compartment Fire Detection System	Opt
Engine Compartment Fire Detection and	_
Automatic Fire Supression System	S
Roof Emergency Exit and Ventilation Hatch	S S S
Fog Lamp (Front)	S

Exterior	
Metallic Paint	Opt
Towing Device	S (Rear)
Doors	
Number of Service Doors	2
Type of Service Doors	Single Wing Outwards Opening

Nulliber of Service Doors	۷
Type of Service Doors	Single Wing Outwards Opening
	(automatic locking system with vehicle speeds above 5km/h)
Remote Control	S (Front and Rear)
Wheelchair Lift or Preparation	Opt
	·

Layers of Glass	Single glazed (S), Double glazed (Opt)
Driver Windows	
Windshield	Single Piece, Tinted
Driver's Window	Manuel (S) Flectrical (Ont) with Heating

Driver's Window Front Door Window Interior Driver Seat	Manuel (S), Electrical (Opt), with Heating Single Glazed with Heating

Driver Seat	With Air Spings, Adjustable
Magony Coating for Dashboard	Opt
Windscreen Blind	Manual (S), Electrically Controlled (Opt)
Side Mirrors	Manual (S), Electrically Controlled with Heating (Opt)
D Ct-	

Cloth on Plastic
Opt
S
S
S
Opt
Opt
S (Aisle Side), Opt (Window Side)
Opt S (2-Points), Opt (3-Points)
S (2-Points), Opt (3-Points)

Safety Belts	S'(2-Points), Opt (3-Points)
Passenger Compartment	
Ceiling Upholstery	Formica (S), Cloth (Opt)
Side Wall Upholstery	Artificial Leather
Overhead Multi-Sets (Crew Call Button, Reading Lamps)	S
Curtains (Passenger Windows)	S
Refrigerator (Vertical)	Opt
Refrigerator (Horizontal)	Opt
Tea/Coffee & Refrigerator Combi Set	Opt*
Audio & Visual	<u> </u>
Sound System	Radio, MP3, SD Card, USB (S), DVD Player (Opt)
Microphone & Amplifier	Opt
Digital Clock	S
LCD Screen (Passenger Compartment)	Opt

*Combi set and Crew seat are not available with

29 passengers seat layout

S: Standart **0:** Optional * Different seating variations are available.













