


ISUZU CITIPORT 12 CNG

CITIPORT 12 CNG

TECHNICAL SPECIFICATIONS

Dimensions (mm)		
Maximum Length Maximum Width Maximum Height	12030 2550 3400 (Including CNG tanks)	
Wheelbase Front Overhang Rear Overhang	5850 2700 3480	
Weights (kg) Gross Vehicle Weight Engine	18700	
Model Type Number of Cylinders Displacement (cc) Maximum Power (kw(HP)/rpm) Maximum Torque (Nm/rpm) Emission Standard Transmission	CUMMINS L9NE6DII320B CNG Turbocharged 6 8900 239 (320) / 2000 1356 /1300-1400 Euro VI OBD-D	
Model Number of Gears Steering System	ZF 6 AP 1400 EMF 6 Forward, 1 Reverse Hydraulic and Adjustable Dashboard and Steering	
TyresTyre Sizes	Wheel Column in Height and Inclination 275/70 R22.5	
Suspension		
Front	Air Suspension - 2 Bellows Independent Suspension Electronically Controlled (ECAS) Air Suspension - 4 Bellows	
Anti Roll Bar Kneeling System (ECAS) Brake System	Electronically Controlled (ECAS) S S	
Front / Rear System	Disc / Disc Full Air Brake System With EBS (Automatic Oil, Water Seperator System is Optional)
Parking Brake Auxiliary Brake Fuel Tank	Air Actuated Acted on Rear Axle Intarder (Retarder is Integrated to Transmission)	,
Gas Tanks Capacity (L) Gas Filling Port Electrical System	S 1470 L (5x294 L), Opt 1175 L (5x235 L) ** Compatible with NGV2 (Both side of vehicle)	
Battery Passenger Capacity*	24V - 2 x 240 Ah	
Standard Layout	27 (24fixed+3foldable) Passenger Seats + 1driver's Seat (Maximum 65 Standing Passengers When Fold Seats Are Closed) (S)	
Layout with Wheelchair	18(s)+70(sta)+1(w)+1(d)	








Driver Speaker

FOUIPMENTS

EQUIPMENTS	
Heating and Ventilation Pre Heater	Ont
Air Conditioner	Opt
Digital Air Conditioner	S
A/C With Heater	Opt
Safety & Driving Comfort	
Speed Limitor	S
Tachograph (Smart)	S
Tachograph (Digital)	Opt
Rear View Camera	S (1 - D)(D)
Interior Camera Exterior Camera	S (Inc. DVR)
Multiplex System	S S
ABS	ς .
ASR	S
EBS	S
Bus Stop Brake (BSB)	S
Hillholder	S
Retarder	S
Parking Sensor	S
Spare Wheel	S S S S S S S S S
Tyre Inflation Unit	5
Reverse Gear Warning Beeper	S S
Engine Compartment Fire Detection System Engine Compartment Fire Detection and Automatic	5
Fire Supression System	Opt
Automatic Engine Oil Refill System	Opt
Fog Lamps	S (Front and Rear)
Day Time Running Lamps (DRL)	S
Locking System	S, (Opt: Square Lock)
Exterior	
Metallic Paint	Opt
Side Stripe Stickers	Opt
Skid Plate	S
Towing Device	S
Doors	2.D
Number of Service Doors	3 Doors
Type of Service Doors	DoubleWing Air Actuated Interior Movement for All Front, Middle and Rear Doors
Wheelchair Ramp	Side Kneeling System and Ramp
Wheelchair Ramp Sensor	S
Remote Control	S (Front Service Door)
Windows — — — — — — — — — — — — — — — — — — —	<u> </u>
Туре	Non-sliding, 1/4 Hinged Passenger Windows,
	Single Piece (S), With Slider, Double Piece (Opt)
Layers of Glass	Single Glazed (S), Double Glazed (Opt)
Interior	
Driver Seat Driver's Seat	Air Actuated, Adjustable
Steering	Adjustable Steering Wheel
Side Mirrors	Electrically Controlled , Heated
Driver's Cabin	Semi Glass (S), Full Glass (Opt)
Driver Overhead Cabinet	S
Coathanger for The Driver	S
Ticket Validator Preperation	Opt
Passenger Compartment	
Handrail Bars	Yellow (S), Grey (Opt), Stainless (Opt)
USB Charger for Passangers	Opt
Lightening & Signalization	Clithar Pouta Display is (C)
Digital Destination Display	Slither Route Display is (S)
	Rear Route Indicator Panel is (S) Colored Front Route Indicator Panel is (Opt)
Audio & Visual	Cotored Front Route indicator Panel IS (Opt)
Radio System	Radio, USB, MP3 (S)
Monitor / LCD Screen (Passenger Compartment)	S
Digital Clock	S
Wifi Preparation	0
Wifi (Internet) Router	0
Driver Speaker	ς



* Different seating variations are available.



**If selected 1175L, max. height of vehicle will increase * Different se